ATHENA PR/W-M




BETACRYL REFRIGERATED COUNTER-TOP

Refrigerated buffet with laminated wood structure and rear mirror to increase visual depth and offer a wider upper shelf. For aesthetic continuity, the compressor unit ventilation grids are cut directly into the wood structure. Capacity modules: 3-4-5-6 GN 1/1 according to model. Electrical lowerable or fix Plexyglas®s sneezeguard (Athena /M). Module with Betacryl® glass counter. Digital thermostat (+2°/ +8°) and LED lighting. Two polyamide castors with brake as standard. GN pans not included.

MEASURE / CAPACITY

3 GN | 4 GN | 5 GN

PANELLING



LAMINATED WOOD
LAM

FINISHES



OLM
LOM




BIRCH
LBE



VEINED WHITE
LBV



WHITE SAND
LWS



FOG
LNE



WALNUT
LNO



WENGÈ
LWE




ANTHRACITE
LAN




VEINED BLACK
LNV




SILVER
LAR




CAPPUCCI-NO
LCP



GREY
LGR



CLAY
LTC




SAGE
LSV




IVY
LER




LIME
LIM




NIAGARA
LNI




OCEAN
LOC




SKY
LSK



ROSE
LRS



SAFFRON
LZA



COLOR TO SCIEGLERE IN THE FUTURE
TO BE DEFINED

OPTIONAL

TRAY HOLDERS


6


7


8


3/FO


6/FO


9/FO


3-A


3-TUB


3-SST


9-A


9-TUBA


9-STTA


9C



9C-SSTC


9C-TUBC

VARIOUS


HZ6



HHTR


5


GN


Z



PZH


45CUT


UK



ADS


TEBT

BACKSPLASHES/RAISED SHELVES



16

BODY



10



4



14



15

EXTENSION



17



17CH

TECHNICAL DATA

Technical data	ATHENA 3	ATHENA 4	ATHENA 5	ATHENA 6
GN Capacity	3	4	5	6
External dimensions (mm)	1174 x 747 x 1515	1499 x 747 x 1515	1824 x 747 x 1515	2149 x 747 x 1515
Net weight (Kg)*	149 R - R/M 197 RV/M 151 PR/M	177 R - R/M 213 RV/M 179 PR/M	198 R - R/M 271 RV/M 181 PR/M	219 R - R/M
Packaging size (cm)	135 x 92 x 185h	155 x 92 x 185h	185 x 92 x 185h	220 x 92 x 185h
Working temperature (°C)	+2 / +8	+2 / +8	+2 / +8	+2 / +8
Refrigerant gas	R290	R290	R290	R290
Power consumption (Watt)	358 R - 598R/M 617 RV/M 598 PR/M	362 R - 602 R/M 630 RV/M 602 PR/M	365,5 R - 605,5R/M 642,5 RV/M 605,5 PR/M	367 R - 607R/M
Supply voltage at 50 Hz (V)	230 V	230 V	230 V	230 V

* Model weight without options

TECHNICAL DRAWING

